

BORG



TECHNICAL SPECIFICATIONS

	Surface mass	DIN EN 12127	315g/m2 ± 5%
	Working width of roll		minimum 140 cm
	Composition	EU 1007/2011	92%PES + 8%PA
	Martindale test	EN ISO 12947-1,2	40 000
	Pilling resistance	EN ISO 12945-2 (2000T)	4
	Colour fastness to light	EN ISO 105-B02-2	4-5
	Colour fastness to dry rubbing	EN ISO 105-X12	4-5
	Colour fastness to wet rubbing	EN ISO 105-X12	4-5
	Tear growth resistance	EN ISO 13937-3	
	Warp		60 N

BORG COLLECTION

fabbb

59	
44	
52	
22	
24	
30	
39	
68	
48	
74	
73	
78	
83	
86	
19	
17	
13	
08	
05	

RAVEN



TECHNICAL SPECIFICATIONS

	Surface mass	DIN EN 12127	400 g/m2 ± 5%
	Working width of roll		minimum 140 cm
	Composition	EU 1007/2011	100%PES
	Martindale test	EN ISO 12947-1,2	50 000
	Pilling resistance	EN ISO 12945-2 (2000T)	4
	Colour fastness to light	EN ISO 105-B02-2	5
	Colour fastness to dry rubbing	EN ISO 105-X12	4-5
	Colour fastness to wet rubbing	EN ISO 105-X12	4
	Tear growth resistance	EN ISO 13937-3	
	Warp		40 N

RAVEN COLLECTION

fabb



MAVEL



TECHNICAL SPECIFICATIONS

	Surface mass	DIN EN 12127	270 g/m2 ± 5%
	Working width of roll		minimum 140 cm
	Composition	EU 1007/2011	100%PES
	Martindale test	EN ISO 12947-1,2	60 000
	Pilling resistance	EN ISO 12945-2 (2000T)	4-5
	Colour fastness to light	EN ISO 105-B02-2	4
	Colour fastness to dry rubbing	EN ISO 105-X12	4-5
	Colour fastness to wet rubbing	EN ISO 105-X12	4
	Tear growth resistance	EN ISO 13937-3	

MAVEL COLLECTION

fabbb

44	
68	
42	
59	
99	
52	
23	
26	
38	
45	
78	
77	
85	
83	
86	
19	
16	
14	
10	
03	